

Surveillance Series Hardware Specification	
Model	UB570G PRO 12G-SDI HDR
Max. Input Resolution	4096×2160p @ 60/50fps
Recording Mode	Software Compression, Real-Time Mode
Product Photo	
Interface	USB3.0 Type B (SuperSpeed) UVC
Video Input Interface	Single Link 12G-SDI or Quad Link 3G-SDI (Option: Dual Link 6G-SDI)
Video Output Interface	1×12G-SDI (Option: Loop-through, For Single Link 12G-SDI)
Video RAW Data Format	YUY2, P010 (Support on outputs below 1080P60) NV12, I420 (Supports on all outputs)
Video Input Resolution	USB3.0 Support Resolution All resolution below 4096×2160p@60fps (Option: 422/420 10Bit HDR)
Recording Video Format	YUY2, P010, NV12, I420 (USB 3.0)
UVC Video Output Resolution	USB3.0 Support Resolution 4096×2160p@60/50fps and 3840×2160p@60/50fps inputs will transfer to 3840×2160p@30fps (NV12, I420) or 1920×1080p@60fps (YUY2, P010) For all inputs below 3840×2160p@30fps,UB570G PRO 12G-SDI HDR outputs will be the same
Audio Input Interface	SDI Embedded Audio 3.5mm Analog Stereo Audio

Audio Output Interface	SDI Embedded Audio
UAC Audio Output Format	Stereo / 16-bit / 48000Hz
System Requirement	
OS Support	Windows 7 / Windows 8 / Windows 8.1 / Windows 10 (32-bit and 64-bit) Linux / MAC OS / Android

Connection Diagram



Device Size

